

# Nexbraid® Reinforced Clear PVC Hose



- Description** Flexible, see through clear hose with braid pattern reinforcement
- Tube and Cover** Flexible clear PVC with transparent blue tint\*
- Reinforcement** 2 Polyester Spirals
- Temp. Range** +25 to +150F / -5 to +65C\*\*
- Applications** Air and water hose, beverage dispensing, potable water, light vacuum, air breathing supply pneumatics, powdered food transfer, flexible conduit and harness.
- Ratings** FDA ingredients\*, NSF 51 certified to 180F (82C)\*\*, USP Class VI Rated\*  
EU: Meets requirements and amendments of Resolution AP(89) for food contact  
RoHS Compliant



## Class 125 Nexbraid® SW – Food and Beverage Grade, Standard Wall

Part No.	I.D.	O.D.	Max. WP PSI at 68F/20C**	Standard Package	APPROXIMATE WEIGHT				Stocked***
					Per 100 Feet Lbs	Per 100 Feet Kgs	Std. Package Lbs	Std. Package Kgs	
125-02000500	1/8	.315	300	500 ft/coil	3.6	1.6	18	8	yes
125-03000300	3/16	.375	250	300 ft/coil	4.5	2.0	14	6	yes
125-04000300	1/4	.438	250	300 ft/coil	5.7	2.6	17	8	yes
125-05000300	5/16	.525	250	300 ft/coil	7.5	3.4	23	10	yes
125-06000300	3/8	.594	225	300 ft/coil	9.0	4.1	27	12	yes
125-08000300	1/2	.750	200	300 ft/coil	13.8	6.3	41	19	yes
125-10000300	5/8	.875	200	300 ft/coil	16.5	7.5	50	22	yes
125-12000300	3/4	1.030	150	300 ft/coil	21.9	9.9	66	30	yes
125-16000200	1	1.300	125	200 ft/coil	31.5	14.3	63	29	yes
125-20000100	1 1/4	1.625	100	100 ft/coil	45.0	20.4	45	20	yes
125-24000100	1 1/2	1.937	100	100 ft/coil	64.0	29.0	64	29	yes
125-32000100	2	2.490	75	100 ft/coil	95.0	43.1	95	43	yes

## Class 126 Nexbraid® HD – Food and Beverage Grade, Heavy Duty Thick Wall

Part No.	I.D.	O.D.	Max. WP PSI at 68F/20C**	Standard Package	APPROXIMATE WEIGHT				Stocked***
					Per 100 Feet Lbs	Per 100 Feet Kgs	Std. Package Lbs	Std. Package Kgs	
126-04000300	1/4	.500	350	300 ft/coil	8.0	3.6	24	11	yes
126-05000300	5/16	.562	275	300 ft/coil	9.3	4.2	28	13	no
126-06000300	3/8	.625	250	300 ft/coil	10.6	4.8	32	14	yes
126-08000300	1/2	.810	250	300 ft/coil	17.5	7.9	53	24	yes
126-10000200	5/8	.995	250	200 ft/coil	26.1	11.8	52	24	no
126-12000200	3/4	1.120	200	200 ft/coil	30.2	13.7	60	27	yes
126-16000200	1	1.370	150	200 ft/coil	39.0	17.7	78	35	yes
126-20000100	1 1/4	1.750	125	100 ft/coil	65.6	29.8	66	30	no
126-24000100	1 1/2	2.000	100	100 ft/coil	76.5	34.7	77	35	no

- Notes**
- \* All tube compound ingredients used in this hose are listed in the U.S. FDA CFR, Title 21. Hose NSF 51 listed. Compound USP Class VI rated.
  - \*\* Working pressures shown are at 68F/ 20C. Higher temperatures reduce the available working pressure. See temperature/pressure chart.
  - \*\*\* Minimum quantity guideline applies for non-stock items. Other sizes, colors and lengths are available on request. Contact Nexgen Hose. Due to our process of continuous improvement, specifications are subject to change without notification.