

Nexlo General Purpose Hose

- Description** General Industrial Service Air Hose
- Tube** Black PVC
- Reinforcement** 2 Polyester Spirals
- Cover** Red PVC. Also available in, yellow (2), blue (6), grey (7) and black (8) covers.
- Temp. Range** +25 to +150F / -5 to +65C *
- Applications** Air and water lines, light vacuum, mold machine water cooling, water soluble chemical spray. Light wall hose available in 1/4 and 3/8 ID.
Coupled assemblies available on special order.
- Ratings** Complies with RMA Class B Designation, Electrically Non-Conductive

SILICONE FREE



Class 150 Nexlo Standard Duty Air Hose

Part No.	I.D.	O.D.	Max. WP PSI at 68F / 20C*	Standard Package	APPROXIMATE WEIGHT				Stocked**
					Per 100 Feet Lbs	Kgs	Std. Package Lbs	Kgs	
150-0400X501	1/4	.500	300	500 ft/reel	8.4	3.8	42	19	yes
150-0500X501	5/16	.562	300	500 ft/reel	9.8	4.4	49	22	yes
150-0600X501	3/8	.625	300	500 ft/reel	11.3	5.1	57	26	yes
150-0800X501	1/2	.750	300	500 ft/reel	14.4	6.5	72	33	yes
150-1000X401	5/8	.875	200	400 ft/reel	18.9	8.6	76	34	yes
150-1200X301	3/4	1.030	200	300 ft/reel	23.3	10.6	70	32	yes
150-1600X301	1	1.312	175	300 ft/reel	34.1	15.5	102	46	yes

To select the part number for a specific color, substitute the "X" with color number from the list below:
Red = 4, Blue = 6, Yellow = 2, Grey = 7, Black = 8

Nextrile Premium PVC Air Hose

- Description** Premium Low Temperature GP Air Hose
- Tube** Prime Black PVC
- Reinforcement** 2 Polyester Spirals
- Cover** Red PVC. Also available in, yellow (2) and blue (6).
- Temp. Range** -22 to +150F / -30C to +65C *
- Features**
 - Designed to look and feel like rubber and remain flexible at lower temperatures
 - Lighter than rubber hose in the same dimensions
 - Cover is non-marking and resistant to UV and ozone attack
 - Supplied in long one piece lengths
- Applications** Excellent air tool hose, air and water lines, mold machine water cooling, water soluble chemical spray, low temperature and other outdoor air applications
- Ratings** Complies with RMA Class B Designation, Electrically Non-Conductive

SILICONE FREE



Class 155 Nextrile – Premium Low Temperature General Purpose Air and Water Hose

Part No.	I.D.	O.D.	Max. WP PSI at 68F / 20C*	Standard Package	Wgt. Per 100 Feet		Package Weight		Stocked**
					Lbs	Kgs	Lbs	Kgs	
155-0400X501	1/4	.500	300	500 ft/reel	8.4	3.8	42	19	yes
155-0500X501	5/16	.625	300	500 ft/reel	13.0	5.9	65	30	yes
155-0600X501	3/8	.625	300	500 ft/reel	11.3	5.1	57	26	yes
155-0800X501	1/2	.775	300	500 ft/reel	15.7	7.1	79	36	yes
155-1000X401	5/8	.890	250	400 ft/reel	18.3	8.3	73	33	no
155-1200X301	3/4	1.080	250	300 ft/reel	26.9	12.2	81	37	yes
155-1600X301	1	1.350	200	300 ft/reel	36.3	16.5	109	49	yes

To select the part number for a specific color, substitute the "X" with color number from the list below:
Red = 4, Yellow = 2, Blue = 6

- Notes** * Working pressures shown are at 68F / 20C. Higher temperatures reduce the available working pressure. See temperature/pressure chart.
** Minimum quantity guideline applies for non-stock items. Other sizes, colors and lengths are available on request. Contact Nexgen Hose.