

Nexspray U Reinforced Spray Hose

- Description** Turf, pesticide, herbicide applicator hose
- Tube** Urethane PVC blend, resistant to hydrocarbon based chemicals (diluted)
- Reinforcement** 4 Polyester Spirals
- Cover** PVC, horizontally ribbed to reduce drag and increase abrasion resistance
- Cover Colors** Class 202 Yellow, Class 203 Green
- Temp. Range** +25 to +150F / -5 to +65C *
- Applications** Herbicide spray, pesticide application, tree spraying, crop spraying

SILICONE FREE



Class 202 Nexspray U600, 600 PSI Ribbed Yellow

Part No.	I.D.	O.D.	Max. WP PSI at 68F / 20C*	Standard Package	APPROXIMATE WEIGHT				Stocked**
					Per 100 Feet Lbs	Per 100 Feet Kgs	Std. Package Lbs	Std. Package Kgs	
202-06002300	3/8	.655	600	300 ft/coil	12.7	5.8	38	17	yes
202-06002400	3/8	.655	600	400 ft/coil	12.7	5.8	51	23	yes
202-08002300	1/2	.840	600	300 ft/coil	20.1	9.1	60	27	yes
202-08002400	1/2	.840	600	400 ft/coil	20.1	9.1	80	36	yes
202-12002300	3/4	1.140	600	300 ft/coil	33.1	15.0	99	45	yes

Class 203 Nexspray U800, 800 PSI Ribbed Green

Part No.	I.D.	O.D.	Max. WP PSI at 68F / 20C*	Standard Package	APPROXIMATE WEIGHT				Stocked**
					Per 100 Feet Lbs	Per 100 Feet Kgs	Std. Package Lbs	Std. Package Kgs	
203-06005300	3/8	.655	800	300 ft/coil	13.0	5.9	39	18	yes
203-08005300	1/2	.840	800	300 ft/coil	20.1	9.1	60	27	yes
203-10005300	5/8	.990	800	300 ft/coil	27.0	12.2	81	37	no
203-12005300	3/4	1.140	800	300 ft/coil	33.6	15.2	101	46	yes

Nexspray Reinforced Spray Hose

- Description** Economical turf, pesticide, herbicide applicator hose
- Tube** PVC
- Reinforcement** 2 Polyester Spirals
- Working Pressure** 600 PSI at 68F (20C)*
- Cover** Yellow or Green PVC, horizontally ribbed to reduce drag and increase abrasion resistance
- Temp. Range** +25 to +150F / -5 to +65C *
- Applications** Herbicide spray, pesticide application, crop spraying. *Not recommended for use with hydrocarbon based spray solutions. See Nexspray U600.*

SILICONE FREE



Class 268 Nexspray PVC Spray Hose, 600 PSI Ribbed Yellow (previously Class 200)

Part No.	I.D.	O.D.	Color	Standard Package	APPROXIMATE WEIGHT				Stocked**
					Per 100 Feet Lbs	Per 100 Feet Kgs	Std. Package Lbs	Std. Package Kgs	
268-06002300	3/8	.635	Yellow	300 ft/coil	11.6	5.3	35	16	yes
268-06002400	3/8	.635	Yellow	400 ft/coil	11.6	5.3	46	21	yes
268-06005300	3/8	.635	Green	300 ft/coil	11.6	5.3	35	16	yes
268-08002300	1/2	.790	Yellow	300 ft/coil	16.8	7.6	50	23	yes
268-08002400	1/2	.790	Yellow	400 ft/coil	16.8	7.6	67	30	yes
268-08005300	1/2	.790	Green	300 ft/coil	16.8	7.6	50	23	yes
268-08005400	1/2	.790	Green	400 ft/coil	16.8	7.6	67	30	yes

Notes * Working pressures shown are at 68F / 20C. Higher temperatures reduce the available working pressure. Contact factory for guideline. Proper coupling procedures must be used to safely obtain working pressures. Screw on reusable couplings and hydraulic couplings are not recommended. Use of these couplings will void the warranty.

** Minimum quantity guideline applies for non-stock items. Other sizes, colors and lengths are available on request. Contact Nexgen Hose.