

# Nexcol Colored PVC Tubing



**Description** General Purpose Colored PVC tubing  
**Tube Material** Colored PVC - 75A Durometer  
**Temp. Range** +25 to +150F / -5 to +65C\*  
**Applications** Drain lines, liquid transfer, low pressure air line, light vacuum, wire harness.  
*Not suitable for fuel.*



## Class 106 Nexcol Colored PVC Tubing

Part Number	I.D.	O.D.	Wall	Max. WP PSI at 68F / 20C*	Color	Standard Package	Package Lbs	Weight Kgs	Stocked **
106-02041702	1/8	1/4	.062	65	white	1000 ft/box	19.0	8.6	yes
106-02048702	1/8	1/4	.062	65	black	1000 ft/box	19.0	8.6	yes
106-03058102	3/16	5/16	.062	55	black	100 ft/box	2.5	1.1	yes
106-04068102	1/4	3/8	.062	55	black	100 ft/box	3.2	1.5	no
106-06088102	3/8	1/2	.062	45	black	100 ft/box	4.5	2.0	no
106-08108102	1/2	5/8	.062	30	black	100 ft/box	5.8	2.6	no
106-08128102	1/2	3/4	.125	45	black	100 ft/box	12.9	5.9	no
106-10145100	5/8	7/8	.125	40	green	100 ft/coil	15.5	7.0	no
106-12166100	3/4	1	.125	35	blue	100 ft/coil	18.1	8.2	yes
106-14187100	7/8	1-1/8	.125	30	grey	100 ft/coil	20.7	9.4	no
106-16208100	1	1-1/4	.125	25	black	100 ft/coil	25.8	11.7	no

# Nexprime T Fuel Grade Tubing

**Description** Fuel Resistant PVC tubing. Resists deteriorating effects of exposure to fuel.  
**Tube Material** Clear PVC with slight amber tint – 70A Durometer  
**Temp. Range** +25 to +150F / -5 to +65C\*  
**Applications** Small engine fuel feed lines where the liquid is normally in continuous contact in the line. *Not suitable for automotive “under the hood” applications.*



## Class 115 Nexprime T Fuel Grade PVC Tubing

Part Number	I.D.	O.D.	Wall	Max. WP PSI at 68F / 20C*	Color	Standard Package	Package Lbs	Weight Kgs	Stocked **
115-02040102	1/8	1/4	.062	65	clear	100 ft/box	1.9	0.9	yes
115-03050102	3/16	5/16	.062	55	clear	100 ft/box	2.5	1.1	yes
115-04060102	1/4	3/8	.062	55	clear	100 ft/box	3.2	1.5	yes
115-06080102	3/8	1/2	.062	45	clear	100 ft/box	4.5	2.0	yes

**Notes** \* Working pressures shown are at 68F / 20C. Higher temperatures reduce the available working pressure. See temperature/pressure chart.  
 \*\* Minimum quantity guideline applies for non-stock items. Other sizes, colors and lengths are available on request. Contact Nexgen Hose.  
 Due to our process of continuous improvement, specifications are subject to change without notification.